

Heavy Equipment Camera System

PART NUMBER:SHV-70M3AV-HT



WITH DISTANCE GRID LINES

7" TFT- LCD color monitor with digital screen

Product: 7" TFT- LCD color monitor digital screen

Audio output: 1W.

Loudspeaker: one 15x24mm round loudspeaker.

Power supply: Automobile storage battery (10-32V).

Power consumption: about 6W .

Outer dimension: 1946.6mm (W) x 128mm (H) x 39.3mm (T)

Dot pitch: 0.192 (H) x 0.1805 (V).

Resolution: 800x3 (RGB) x 480.

Contrast: 500:1.

Brightness: 400 cd/ m².

Viewing angle: U: 50° / D: 60°, R/L: 70° /70°

Operating temperature: -20°C—+70°C, RH90%.

Storage temperature: -30°C—+80°C, RH90%

15 G-force rated shock resistant for the monitor



INTERNAL HEATER

1/3" COLOR CCD SENSOR SPECIFICATIONS

With Audio and IR

Image Device: SHARP

TV System: PAL/NTSC

Effective Pixels: 512x582 pixels / 512x492 pixels

Scanning System:2:1 Interlace

Resolution: 420TV lines

Minimum Illumination: 0 Lux/F1.2 with IR

Microphone: Included

Video Output: 1.0vp-p, 750hm

S/N Ratio: Better than 48dB

Current Consumption: Max. 300mA

Operating Temperature: -30°C-70°C, RH95% MAX

Storage Temperature: -40°C-80°C, RH95% MAX

Lens: f=3.6mm / 2.8mm F=2.0

Lens Angle 120°

15G-force rated shock resistant for the camera



CALL TOLL FREE: 1-888-434-0253 — CONTACT: SALES@PROVIX.NET — VISIT: WWW.PROVIX.NET